

產品名稱 / Description	100 系列路燈 / 100W Series Street Light			
產品型號 / Model Number	HPL-100-S2-W1		HPL-100-S2-W2	
發光元件 / Light Source	高亮度 LED 發光體 (High-brightness LED emitters)		超高亮度 LED 發光體 (Super High-brightness LED emitters)	
燈具光通量 / Rated Net Luminous Output from Luminaire	6000Lm (typ.)		8000Lm (typ.)	
抵達路面光通量 Total Luminous Flux on Roadway	4000Lm (typ.)		5350Lm (typ.)	
相當於或可取代 Equals to or Replaces	200W 高壓鈉燈(Sodium lamp) 250W 水銀燈(Mercury lamp)		250W 高壓鈉燈(Sodium lamp) 300W 水銀燈(Mercury lamp)	
輸入電壓 / Input Voltage	48V 直流(DC)		48V 直流(DC)	
輸入電流 / Input Current	2.1A 直流(DC)		2.1A 直流(DC)	
輸入功率 / Input Power	100W (typ.)		100W (typ.)	
燈源安裝高度 ( Luminaire Height )	照度 ( Illumination )	照射範圍 ( Coverage Area )	照度 ( Illumination )	照射範圍 ( Coverage Area )
7 米(m)	31Lux	38m dia	46Lux	38m dia ( $\phi$ )
8 米(m)	24Lux	44m dia	35Lux	44m dia ( $\phi$ )
9 米(m)	19Lux	50m dia	28Lux	50m dia ( $\phi$ )
10 米(m)	15Lux	55m dia	23Lux	55m dia ( $\phi$ )
11 米(m)	12Lux	60m dia	19Lux	60m dia ( $\phi$ )
12 米(m)	10Lux	66m dia	16Lux	66m dia ( $\phi$ )
專利散熱技術 Patented Heat Dissipation Technology	迴路熱管 / Loop Heat Pipe (LHP)			
操作環境溫度 / Operating Ambient Temp	(-30°C ~ 40°C)			
防水等級 / Water Proof	全密閉防塵防水(>IP65) Fully sealed, >IP65		全密閉防塵防水(>IP65) Fully sealed, >IP66	
產品壽命 / Lifetime	>50,000Hrs			
外型尺寸 / Dimensions	580 x 250 x 120mm			
重量 / Weight	4.5kg			
產品規格若有變更恕不另行通知 / specifications subject to change without prior notice				

