

SPECIFICATION FOR COTCO LED LAMP

MODEL No : LC503PYA1-30Q-A
DOC. No : B 03Aug04


Description:

30 Degree 5mm Round LED Lamp in Amber
Color with Water Transparent Lens and No
Stopper

Dice Material: AlGaInP

Confirmed
by Customer: _____

Date: _____



COTCO LUMINANT DEVICE (HUIZHOU) LTD.

Model No.	LC503PYA1-30Q-A
Doc. No.	B 03Aug04

Applications:

- Advertising Signs
- Indicators
- Automotive Lighting

Absolute Maximum Ratings at Ta = 25°C

Items	Symbol	Absolute maximum Rating	Unit
Forward Current ^{*2}	I _F	50	mA
Peak Forward Current ^{*1}	I _{FP}	200	mA
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	125	mW
Operation Temperature	T _{opr}	-40 ~ + 95	°C
Storage Temperature	T _{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T _{sol}	Max.260°C for 3 sec Max. (3mm from the base of the epoxy bulb)	


*1 pulse width <=0.1msec duty <=1/10

*2 For long term performance the drive currents between 10mA and 30mA are recommended. Please contact COTCO sales representative for more information on recommended drive conditions.

Typical Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V _F	I _F = 20mA	---	2.0	2.5	V
Reverse Current	I _R	V _R = 5V	---	---	100	μA
Dominant Wavelength	λ _D	I _F = 20mA	592	596	600	nm
Luminous Intensity	I _v	I _F = 20mA	1520	2600	---	mcd
50% Power Angle	20½H-H	I _F = 20mA	---	30	---	deg

Dimension Drawing



Model No.	LC503PYA1-30Q-A
Doc. No.	B 03Aug04


Standard bins for LC503PYA1-30Q-A ($I_F = 20\text{mA}$):

Lamps are sorted to Luminous Intensity – I_V , & Dominant Wavelength – λ_D bins shown.

Orders for LC503PYA1-30Q-A may be filled with any or all bins contained as below.

All Luminous Intensity – I_V , & Dominant Wavelength – λ_D values shown and specified are at $I_F=20\text{mA}$.

* U+



* U+ indicates Luminous Intensity is at U bin or above.

Important Notes:

- 1) All ranks will be included per delivery, rank ratio will be determined by Cotco.
- 2) Pb content <1000PPM.
- 3) Tolerance of measurement of luminous intensity is $\pm 15\%$.
- 4) Tolerance of measurement of dominant wavelength is $\pm 1\text{nm}$.
- 5) Tolerance of measurement of V_f is $\pm 0.05\text{V}$.
- 6) Packaging methods are available for selection, Please refer to PACKAGING STANDARD.
- 7) Please refer to LED LAMP RELIABILITY TEST STANDARD for reliability test conditions.

Model No.	LC503PYA1-30Q-A
Doc. No.	B 03Aug04

Graphs




FIG.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS. REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT.




FIG.4 RELATIVE LUMINOUS INTENSITY VS. WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS AMBIENT TEMPERATURE ($T_{jmax}=105^{\circ}\text{C}$)




FIG.6 FAR FIELD PATTERN

Items	Signatures	Date	Revision History	
Prepared by	LiuZM	2004/08/03	DOC. No.	CHANGE DESCRIPTION
Checked by	AldosinLi	2004/08/03	B 03Aug04	Add ESD and Notes; Change FIG.1&3&5; Change IV & λ_D Rank form.
Approved by	David	2004/08/03		
ECN#	ECN-H20040190			

Data is subject to change without prior notice.

Copyright©2002 Cotco International Ltd.

Obsoletes Doc: A 11Feb04.